

Panasonic BB-HCM331CE network-camera 640 x 480

BRAKENSIEK®
SYSTEMHAUS



Panasonic BB-HCM331CE network camera 640 x 480

Non-new

Type: Outdoor with linguistic recording

Picture compression: JPEG

Videoresolution: 320 x 240 (default), 160 x 120

Image quality: (Favor Clarity, standard, Favor inflexion)

Framerate: Max. 30 frames/sec (320 x 240, 160 x 120), max. 12 frames/sec (640 x 480)

Security: UserID, password, IPsec

Encoding algorithm: DES-CBC, 3DES-CBC, AES-CBC

IP Sec function: ESP Encryption, EP Authentication, transport fashion (only the Main fashion) / tunnel fashion, IKE (Internet Key Exchange)

Supported protocols: IPv4 / IPv6 binary stack; IPv4: TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, IPsec, UpnP; IPv6: TCP, UDP, IP, HTTP, FTP, SMTP, DNS, ICMPv6, POP3, NDP, NTP, IPsec

Max user accesses: 30 accesses (from this 10 accesses with linguistic recording)

Buffer for pictures: Approx. 125 pictures: (320 x 240), standard image quality (approx. 16 KB per picture) (without use of a SD Memory Card)

View corner: 53 ° horizontally (Totally 173 °), 40 ° vertically (full shot 105 °)

Max Neigungsgeschwindigkeit: Pan: Max. 80°/sec, Tilt: Max. 80°/sec

Pixel number: approx. 320,000 pixels

Light intensity: From 3 to 100,000 luxes (in the Color Night View fashion: From 0.2 to 100,000 luxes)

Linguistic direction: Half-Duplex Two-Way Communication (Transceiver system)

Linguistic compression: ADPCM 32 kbps

Audio-entrance: Internal or external (separately available) microphone, external connection more than 3.5 mm of mini handle plug

Audio-exit: Audio Line output terminal for external loudspeaker (3.5 mm In stereo mini handle plug, monauraler exit)

SD Memory Card slot: Full Size (functioned with 1 GB, 512 mb, 256 mb, 128 mb and 64 mb SD Memory Cards)

Stream connection: AC adaptor: Input 120 V of AC, output 12 V DC

Power consumption: 6 W

Device kind

Network camera Yes

Technology

Picture converter 1/4" CCD

Videoresolution 640 x 480

Min density of light 3 luxes

Equipment

Wheel and Neigekopf automat. Yes

Microphone integrates

Interfaces

Network 10Base-T; 100Base-TX

General data

Dimensions (BxHxT) 100 x 100 x 73.5 mm

Weight 0,310 kg



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MWSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG
Klönnestraße 94
D-44143 Dortmund**

www.brakensiek.com

 **+49(0)231.985-00 10**

 **+49(0)231.985-2000**

BRAKENSIEK®
SYSTEMHAUS

Tim Brakensiek