

DTP45 Spectral photometer



DTP45 Spectral photometer

- Removable head for single measurements
 - L*a*b* announcement
 - Service with only one key
- I-ntegrierter Kalibrierstandard

Exact colour of the monitor up to the final issue

They have the job to provide for the quality of your colour deductions. Hence, you look for an automatic system which saves time you in the pressure preliminary stage workflow and avoids wastepaper. X-Rite has the right solutions for you. With our new X-RiteColor of ensemble and ensembles + you receive a payable, adaptable method for the measurement, verification and correction of your Proofs.

Hardware options for the most different demands

X-RiteColor ensembles offer you the choice between two extremely high-quality Auto-scan spectral photometers, the series DTP41 II and the DTP45, enlargements rich in function of the model DTP41. Both devices use spectral data for the colour measurement with unmatched exactness. Both devices measure test stripe in approx. 20 seconds and transfer the data automatically to your shaping software.

In addition, the model DTP45 offers you, nevertheless, still many other functions, for example, the additional possibility for the realisation of single measurements. Single measurements are often used for large-size media and pressure controlling elements which are not given as a stripe. Thanks to his raised versatility the DTP45 is suitable ideally for all those which need an automatic colour measuring solution for the pressure preliminary stage in one single device.

Highly competitive, practical software options

The ensembles friendly to operator of X-Rite offer them practical, absolutely unproblematic procedures for the colour management and effortless work. They have the choice between two highly competitive software versions: MonacoPROFILER software (gold or Platinum version) – shaping solution ICC, from now on with improved shaping engine and other improvements.

Technical data

Measuring geometry

45 °/0 ° after ANSI/ISO 5-4
(IT2.17) (Reflektion)

Measuring screen size

1.8 mm in scan direction,
2.5-mm width

Source of light

Gas pressure with 2850 K

Spectral sensor

DRS technology, 24-point engine,
31-point issue
Spectral range
400 nm to 700 nm

Light kind

A, C, D50, D55, D65, D75,
F2, F7, F11 and F12

Standard observer

2 ° and 10 °

Density kinds

Status t, E, I, A, M and others

Measuring duration

Approx. 0.25 sec. per measuring field
(7 mm of measuring fields)

Interface

USB

User interface

According to buttons and
LED functions of the DTP41

Display

LCD display with 2 lines a 16
Signs to the announcement from L*a*b*
Value kind and light kind, more use-determinably
Announcement string with
to inlaid device

Measuring options

Stripe measurement and single measurement

Stripe mode

Compatibly to DTP41 stripe

Single mode

Removable hand device with
to foldable down target window

Reflection measurement

Device correspondence
0.3 DE cmc typ.
Durchschn. (on the basis of
from 12 tiles BCRA)

Measuring area

0.00 D to 2.50 D; 0
to 160% R

Ability for reproduction
on white

0.2 DE max.; $\pm 0,01$ D
max.

Linearity

± 0.01 D or 1%

Calibration

Integrated Reflektionsstandard

Surroundings terms

from +10 to +40 °C
Operating temperature, from 30 to 85%
rel. Air humidity, not
condensing

Warm-up time
None

Necessary one
Electricity supply
12 V of direct current, the universal
100-240 V of net part; 50/60 hertz

Dimensions
Height: 104 mm; width: 302 mm;
Depth: 1.184 mm

Weight
1189 g



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MWSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG
Klönnestraße 94
D-44143 Dortmund**

www.brakensiek.com

 **+49(0)231.985-00 10**

 **+49(0)231.985-2000**

BRAKENSIEK®
SYSTEMHAUS

Tim Brakensiek