

Densitometer D19C

BRAKENSIEK®
SYSTEMHAUS



Densitometer D19C

Reflecting densitometer for the measurement of printing

The D19C unites mature measuring technology with an easy service and high loading capacity:

- exact positioning by extendable measuring head
- high-quality, patented ring optics
- Software for the controlled, sure use of the measuring functions
- Polarisation filter
- for Right and left-hander swivelling announcement
- high-resolution display capable of graphics

D19C technical data

Service: Operating wheel and measuring key

Announcement: Digitally LCD, 160 x 128 pixels, full graphics

Measuring geometry: 0°/45°-ring optics

Source of light: Electric light bulb, approx. in 2856 K

Spectral filter: Filter sentence 47 B German Institute for Standardization 16536

Filter sentence 47 status ANSI t

Filter sentence NB German Institute for Standardization 16536 Interference filter

Filter sentence SPI ISO status I Interference filter

Measuring area: 0.00 D - 2.50 D

Ability for reproduction: $\pm 0,01$ D

$\pm 1\%$ for surface cover

Linearity: $\pm 0,01$ D resp. $\pm 1\%$

Copy dispersion: $\pm 0,02$ D resp. $\pm 2\%$

Measuring screen: \varnothing 3.6 mm

Comparison: Steepness: for density measurement

Zero: automatically

Polarisation filter: 2x linearly (Tubus P)

Anwärmzeit: none

Electricity supply: Accumulator NiMH, nom. 7.2 V, in 1000 mAh

Accumulator NiCd, nom. 7.2 V, 600 mAh

Loading time: approx. 3 h, automatic disconnection

Loading state: autom. Control and announcement of the capacity, additional lithium battery for data memory

Measurements per load: approx. in 6000 (with accumulator NiMH)

Measuring time: approx. 0.8 sec

Data interface: RS232, remote control of the densitometer by a computer possibly (exact documents on inquiry)

Clock: Date and exact time

Weight: approx. 890 g

Dimensions: 8.3 x 8.0 x 24.5 cm

Accessories: Standard map, battery charger, operating instructions

BRAKENSIEK®
SYSTEMHAUS



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MwSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG**
Klönnestraße 94
D-44143 Dortmund

BRAKENSIEK®
SYSTEMHAUS



www.brakensiek.com

Tim Brakensiek



 **+49(0)231.985-00 10**



 **+49(0)231.985-2000**