

Linotype-Hell Linotronic 560



Linotype-Hell Linotronic 560

The alternative to Screen Katana, screen 3050 or Heidelberg Hercules Avantra 30 or if no punch is needed and to get along with the material width.

Non-new

Specifications:

System Description: Precision laser recorder

Dimensions (W x H x D): 103 x 95.5 x 81.5 cm

Image area: 457.5 mm, 108 pica (exposure length depending on application)

Resolution: 167-1333 pixels / cm

Speed: 120.4 to 7.5 cm / min

NV parameters such as those necessary for operation with a Harlequin 7.2 RIP are:

To arrive at these values ??need to expand the Rec 1 card and put the bridge B3, and starting a special key combination. This should take only an experienced service technician.

Setting Li5

9600

8 bits

1 stop bit

No parity

RTS / CTS

Setting Li2

By Panel and Li5

Asynchronous

16/8

Menu ADUJUST PARAMETERS:

PG_RES \$ 1E 0000

PG_TFAK (\$ 16F9)

OPTIC (\$ 9D)

SOL (\$ AU)

FLM_RES \$ 140,000

FLM_TFAK (\$ B80)

Menu MACHINE PARAMETERS:

ECLOSZ 315000000

PG_RPM 3344

PG_MAX 4600

PG_MIN 1400

TC_RPM 1442

TC_GN 1800

SOL_T1 450

SOL_T2 550

IM_CUT 132 000

WP_RAM 8

NC_1 \$ 0

SOFTWARE PARAMETERS Menu

EEPROM_BLOCK 0
V_ADV_CUT 220 000
V_ADV_OLP 150 000
V_OLP_MAX 800 000
V_OLP_MIN 200 000
V_TKUP 30000000
SW_YVAL 2000
SW_DELAY 0
POWER_Time 0
EN_REC_TIME \$ FF
STP_MMZM \$ 0
SS_MODE 0
NC_2 \$ 0

Menu MACHINE-TYPE

Recorder R1
Set1 560

Resolution Set Menu

X_Res \$ 78,000
OD_Res \$ F0000
OP_RNG \$ A
DS_RNG \$ 6

Menu-Adjust hardware

Density 450
Res 1333 l / cm

Type of material for test run

F-Width = 456 mm
F-Thik 0.1

Machine test instructions:

Press Service
Switch on the machine
Press Enter 3 times

If no error is present then at the end
P00000/E00269 / # 710 / C
Duration: 15 minutes

We recommend any change to update the NV-RAM data, since the buffer Batterie on the motherboard of the machine is empty and then at some point, the parameters are gone. These values ??will only work with this machine. For other machines, the values ??must be adjusted may be very costly. This requires an oscilloscope my 2x 100 Mhz, about 2 days and plenty of rest and patience.

Note: The on / off switch disconnects the power supply is not 100%. So please pull the plug from the socket in the evening around the machine to protect against surges.

BRAKENSIEK®
SYSTEMHAUS



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MWSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG
Klönnestraße 94
D-44143 Dortmund**

www.brakensiek.com

 **+49(0)231.985-00 10**

 **+49(0)231.985-2000**

BRAKENSIEK®
SYSTEMHAUS

Tim Brakensiek