

X-Rite Eye One Display 2



X-Rite Eye One Display 2

With the increasing popularity of digital photography is increasingly asked to monitor the requirement of a constant, predictable color reproduction.

GretagMacbeth offers with the Eye-One Display 2 is a simple and largely automated color management solution for monitors, which makes manual adjustment of brightness, contrast, white point and monitor unnecessary.

The profiling is done with a single touch, despite the ease of the calibration tool but will not compromise on precision, versatility and functions.

The Eye-One Display 2 features a new sensor, which compared to the previous higher repeatability, faster measurements, a higher sensitivity in low light areas and a more neutral gray scale features.

Included is the enhanced Eye-One Match 3.0 software, which many new features like a new color-matching formula, custom luminance settings and has a new gray balance optimization function.

The package is Mac and Windows compatible.

Specifications

General

Interface: USB * data and power supply

Data format: luminance Y **: cd/m2 * chroma: x, y ** (** CIE XYZ, according to CIE 1931)

Refresh rate Monitor frequencies: 40 Hz to 150 Hz

Cycle time Time per measurement: typical 1 second per patch

Physical dimensions Length 84mm, width 64mm, 35mm (3.3 x 2.5 x 1.4 in) height

Weight 52 g (1.9 oz)

Performance

Dynamic range Black point: 0.05 cd/m2

White point: up to 1,000 cd/m2

Accuracy (LCD) Luminance: Y: typical + / - 2%

Chroma x, y: typical + / - 0.006

Accuracy (CRT) Luminance: Y: typical + / - 2%

Chroma x, y: typical + / - 0.004

Repeatability Luminance: Y: typical + / - 1%

Chroma x, y: typical + / - 0.002

Color temperature CCT (correlated color temperature)

range: typical 4000K to 120000K

accuracy: typical + / - 250K

Measurement conditions

The above are specifications of the Eye-One Display where:

First Sensor is housed in CL skins with proper adapter attached for measurement

Second Accuracy values ??are given relative to the NIST-certified reference at manufacturer

Third Repeatability measurements are stated for same-sensor/no-dismount situation

4th All measurements are dark current corrected

5th Room temperature of 20 degrees C, + / - 5 degrees

6th CRT display is set to white of D50 (x.346, y.359) in a darkened room, luminance is set to 80 cd/m2 or greater at full white, at EBU or P22 phosphor set

7th LCD display is set to white of D65 (x.313, y.329) in a darkened room, luminance is set to 120 cd/m2 or greater at full white

System Requirements

Macintosh ®

Mac OS X (10.2 or higher)

Apple® ColorSync® or higher 3:03
128 MB of available RAM
80 MB of available hard disk space
Monitor resolution of 1024 x 768 pixels or higher
USB support

Windows®
Windows® 2000 or XP
Processor: Pentium® II, 266 Mhz or higher
128 MB of available RAM
80 MB of available hard disk space
Monitor resolution of 1024 x 768 pixels or higher

Power Conditions

Powered by USB, no additional charger required: USB low power class device

Neu! Halten Sie zum Ändern der Reihenfolge die Umschalttaste gedrückt, klicken Sie und ziehen Sie die obigen Wörter. Schließen

Google Übersetzer für Unternehmen:Translator ToolkitWebsite-ÜbersetzerGlobal Market Finder

Sofortübersetzung deaktivierenÜber Google ÜbersetzerMobilDatenschutzHilfeFeedback geben

BRAKENSIEK®
SYSTEMHAUS



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MWSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG
Klönnestraße 94
D-44143 Dortmund**

www.brakensiek.com

 **+49(0)231.985-00 10**

 **+49(0)231.985-2000**

BRAKENSIEK®
SYSTEMHAUS

Tim Brakensiek