

# Linotype-Hell Linotronic 330 + RIP 50



## Linotype-Hell Linotronic 330 + RIP 50

Non-new

### Specifications

- Exposure System: Capstan
- Light source: helium-neon laser with emission of 670-680nm
- Resolution: 635; 846; 1270; 1693: 2032; 2540; 3387 dpi
- Max grid frequency at film exposure: up to 80 lines / cm (175 lpi)
- Repeatability about 5% in size 30 x 30cm
- Output options: positive, negative, right, wrong way
- Materials in rolls: Film, Paper, 0.1 - 0.18 mm at 633 nm
- Capacity of supply cassette max. 60m at 0.10 mm thick photographic material
- Maximum Exposure :: Format 305 x infinity
- Material film widths: 150, 200, 250, 280, and 310 mm
- Dimensions: 75 x 94.5 x 80 cm
- Weight (net): 220 kg
- Interfaces: LI2 x, 2 x LI5

## Linotype-Hell RIP 50

Non-new

### Specifications

Linotronic imagesetter for 260/330/560/630 Hercules and Hercules M  
System Description: Raster Image Processor in stand-alone tower  
3.5 "floppy disk for software maintenance  
Input interfaces: RS 232, Centronics, LocalTalk  
Ethernet, SCSI for external disk  
Outputs: LI2, LI5, SpeedWay  
Grid technologies Original PostScript Level 2 Interpreter from Adobe  
Control over Output Manager from Mac or PC  
Dimensions (W x H x D) 36 x 64 x 55 mm  
Weight about 27 kg

### Technical Data

Light source: 3mW helium neon gas laser

Exposure system: Rotating polygon mirror

Control: Via the LI 2 and LI 5 interfaces

Ports/interfaces: LI 2 interface, LI 5 interface, power input

Optional: Connection for on-line processor

### Output format:

Horizontal: 305 mm (12 inch or 72 Pica) maximum scanline length

Vertical: With take-up cassette: 30 m or 100 feet (Maximum length, if using a HeNe laser film of 0.1 mm or 4 mil)

thickness and 310 mm or 12.2 inch width. In general, the vertical format depends on the RIP and front-end system)

With on-line processor connected: variable lengths up to maximum 800 mm or 31.5 inch can be defined according to the instructions of the processor manufacturer.

Photomaterial: Red-sensitive high speed imagesetting materials with maximum sensitivity at 632 nm and high contrast. Materials: polyester-based HN-laser film, HN RC-paper, HN-direct plate-making materials (printing foils)

Photomaterial supply from: Roller material, emulsion inside; light-proof packaging; wound core diameter 50.4 mm or 2 inches

Required density: Minimum log D 3; follow the density recommendations of the photomaterial manufacturer and select the corresponding density value on the input panel of the laser imagesetter.

Material thickness: 0.10 mm to 0.19 mm or 4 mil to 7 mil

Material widths: 150 mm, 200 mm, 250 mm, 280 mm and 310 mm  
5.9 inch, 7.9 inch, 9.8 inch, 11.0 inch, 12.2 inch

Spot size: 20 µm or 0.8 mil

Addressability (Resolution): In vertical and horizontal direction

3387 dpi (1333 pixel/cm)\*  
2540 dpi (1000 pixel/cm)  
2032 dpi (800 pixel/cm)  
1693 dpi (666 pixel/cm)  
1270 dpi (500 pixel/cm)  
846 dpi (333 pixel/cm)  
635 dpi (250 pixel/cm)

A PostScript RIP 4 or PostScript RIP 300 with software version 51.8 upwards is required to achieve all above resolution steps. (The resolution step marked with \* can be used only in LI 2 asynchronous mode with a 16 MHz clock.)

#### **Maximum recorder Speeds:**

Speed cm/min.: 9.7  
Speed inch/min.: 3.8  
Resolution dpi: 3387  
Resolution pixel/cm: 1333

Speed cm/min.: 17.3  
Speed inch/min.: 6.8  
Resolution dpi: 2540  
Resolution pixel/cm: 1000

Speed cm/min.: 27.1  
Speed inch/min.: 10.7  
Resolution dpi: 2032  
Resolution pixel/cm: 800

Speed cm/min.: 39.0  
Speed inch/min.: 15.4

Resolution dpi:1693  
Resolution pixel/cm:666

Speed cm/min.:34.7  
Speed inch/min.: 13.7  
Resolution dpi:1270  
Resolution pixel/cm:500

Speed cm/min.:78.0  
Speed inch/min.: 30.7  
Resolution dpi:846  
Resolution pixel/cm:333

Speed cm/min.:69.6  
Speed inch/min.: 27.4  
Resolution dpi:635  
Resolution pixel/cm:250





Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MwSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.

Mitglied der

**Brakensiek Systemhaus  
GmbH & Co. KG  
Klönnestraße 94  
D-44143 Dortmund****BRAKENSIEK®**  
**SYSTEMHAUS**

Mitglied im

**[www.brakensiek.com](http://www.brakensiek.com)****Tim Brakensiek**

Mitglied des



+49(0)231.985-00 10

Premium Partner



+49(0)231.985-2000