

X-Rite DTP 70 X-Y AutoScan Spectrophotometer



X-Rite DTP70

not-new, not actual certificated

tested, cleaned, inspected

Instrument Description

The DTP70 X-Y AutoScan Spectrophotometer is designed for on-demand and prepress professionals. This product dramatically reduces the time and difficulty in the process of measuring ICC color management test forms. The instrument reports densitometric, colorimetric and spectral data.

Instrument Specifications

General:

- Measurement Geometry: Reflection 45°/0° per ANSI/ISO 5-4 (IT2.17)
- Spot Size: 3.2 mm diameter
- Light Source: Gas pressure @ 2850°K
- Spectral Sensor: FAST technology, 16-point engine, 31-point reporting
- Spectral Range: 400 – 700 nm
- Illuminant Types: A, C, D50, D65, D75, F2, F7, F11 & F12
- Standard Observer: 2° & 10°
- Density Responses: Status T, E, I, A, Spectral, HiFi, Hexachrome

Measurement Speed:

- 100 measurements per second
- T8 7/3: 2.5 minutes minimum
- ECI: 4.2 minutes minimum
- T8 7/4: 4.5 minutes minimum

Inter-instrument agreement:

- (based on DTP70 standard for 12 BCRA tiles): 0.3 deltaE 94 average; 0.5 deltaE 94 maximum
- Measurement range: 0.00D to 2.50D; 0 to 160% R (reflection)
- Repeatability on White: 0.2 deltaE max.; ±0.01D max.
- Linearity: ±0.02D or 2%, 0 to 2.5D
- Media Thickness: 0.08 mm (0.003 in) to 0.36mm (.014 in)
- Physical filter: UV in / ex – field switchable
- Backer Tray: Black / White – field switchable
- Data Interface: USB 2.0 certified full-speed peripheral device
- Calibration: Internal calibration reference provided
- Warm-up Time: None
- Physical Dimensions: W: 315 mm (12.4 in), D: 193 mm (7.6 in),
-H: 150 mm (5.9 in)
- Weight: 3320 g (7.32 lbs.)

Environmental:

- Operating Temp: +10° (50°F) to +35°C (95°F)
- Humidity Range: 0 - 85% RH non-condensing
- Usage: Indoor Only
- Altitude: 2000m
- Pollution Degree: 2
- Transient Overvoltage: Category II

Accessories Included:

- Calibration Reference (built in)
- DTP Series Manuals
- USB Communication Cable
- Auto-Ranging Power Supply (P/N SE30-77): 100-240VAC, 50-60 Hz; 30W

- UV excluded & UV included optics covers (built in)



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MWSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG**
Klönnestraße 94
D-44143 Dortmund

www.brakensiek.com

☎ **+49(0)231.985-00 10**

📠 **+49(0)231.985-2000**

BRAKENSIEK®
SYSTEMHAUS

Tim Brakensiek