

# Kodak I65 Dokumentenscanner Duplex

**BRAKENSIEK®**  
SYSTEMHAUS



## Kodak I65 Document Scanner Duplex

If you already have Adobe Acrobat, it can scan directly into Acrobat. Adobe Acrobat is not there.

### Non-new

Kodak i65 - Document scanner - 600 dpi x 600 dpi - ADF (75 sheets) - up to 1500  
Scans / day - Fast SCSI / Hi-Speed ??USB

### General

Type: Document scanner - desktop

Width: 56.7 cm

Depth: 35 cm

Height: 19.9 cm

Weight: 7.6 kg

### Scanner

Input Type: Color

Grayscale Depth (External): 8 bits (256 gray levels)

Color Depth (External) 24-bit (16.7 million colors)

Optical Resolution: 600 dpi x 600 dpi

Interpolated Resolution: 600 dpi x 600 dpi

Scan mode: Single-/Duplex-Pass

Scan Element Type: CCD

Bulb / Light Source:

White fluorescent cold cathode lamp

Capacity: 1500 scans / day

### Scanner Speed ??Details:

36 pages / min. - Portrait B / W - A4 - 200 dpi

32 pages / min. - Portrait (grayscale) - A4 - 200 dpi

25 pages / min. - Portrait color - A4 - 150 dpi

50 images / min. - Portrait color - A4 - 150 dpi

64 frames / min. - Portrait (grayscale) - A4 - 200 dpi

72 frames / min. - Portrait B / W - A4 - 200 dpi

Compliant Standards: TWAIN, ISIS

### Media handling

Max Document Size: 216 mm (Legal) x 297 mm (A4)

Supported Media Type: Plain paper

Media Feeder Type: Autoload

Document Storage Capacity: 75 sheets

### Expansion / connectivity

Interfaces:

1 x Fast SCSI - HD D-Sub (HD-50), 50-pin

1 x Hi-Speed ??USB

### Miscellaneous

Accessories: Automatic Document Feeder

Cables Included: 1 x USB cable

### Standards: #

FCC Class B certified, CE, UL, TUV GS, C-Tick, BSMI, VCCI Class B ITE, cUL, EN 61000-3-2, EPA Energy Star,

EN 61000-3-3, EN55024, EN55022 Class B

Power supply

Power Device: Power adapter - external

Voltage Required:

AC 120/230 V (50/60 Hz)

Power Consumption Operational (Standby):

40 watts (12 watts)

Software / System Requirements

Software Included: Drivers & Utilities

OS Required: Microsoft Windows 98SE/2000/ME/XP

System Requirements Details: Windows 98SE/2000/ME/XP - 1 GHz - RAM 512 MB

Environmental conditions

Min Operating Temperature: 10 ° C

Maximum operating temperature: 35 ° C

Humidity Range Operating 20 - 85%

Noise level: 20.6 dBA



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MWSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.

Mitglied der

**Brakensiek Systemhaus  
GmbH & Co. KG**  
**Klönnestraße 94**  
**D-44143 Dortmund****BRAKENSIEK®**  
**SYSTEMHAUS**

Mitglied im

**[www.brakensiek.com](http://www.brakensiek.com)****Tim Brakensiek**

Mitglied des

 **+49(0)231.985-00 10**

Premium Partner

 **+49(0)231.985-2000**