

Heidelberg Herkules Basic Filmbelichter / Imagesetter



Heidelberg Hercules Basic imagesetter / imagesetter

Non-New / Used

Type: 2130

Year of Manufacture: 1998

Professional imagesetter for Printing Machines with format size such as: Heidelberg Speedmaster 74 and Heidelberg Speedmaster 52

Including Bacher Control 2000 punch (Europe) at the long side

Indrum Imagesetter

- Resolution: 3387 dpi
- Size: 750 x 558 mm
- Punch: Bacher Control 2000 (Europe)

Using the punch Bacher Control 2000 (Europe) offers the following advantages:

Two Hercules films fit perfectly into the 70 x 100 cm format press.

You will not get any vibration, even at high speeds of the investigated rotating mirror unit (32,000 revolutions per minute.)

As well as the standard resolutions (1270.1693, 2540 and 3387 dpi),
Herkules BASIC gives you so 2032 and 846 dpi resolutions for high-speed results.

The user-friendly interface on Herkules BASIC makes imaging delightfully simple. Self-explanatory pictograms, icons and graphics give you direct access to important functions like cutting, loading or unloading the drum films.

In other auctions we also offer Heidelberg Delta Technology RIP, RIP Heidelberg MetaDimension, Glunz & Jensen Processor Type 860 online and spare parts for this machine. We always have about 10 Hercules Imagesetters from different manufacturing years on stock.

Please visit our ebay shop.

Heidelberg Herkules Basic

One is you like the Hercules BASIC particularly well:

its speed. He exposed 533 scan lines per second, which are 32 000 revolutions per minute, identical with the same number of revolutions of the deflector.

That in spite of these extreme speeds no vibrations, is due to the superior know-how our engineers. Know-how and do-how that benefits you: in just 70 seconds, four A4 pages with a resolution of 1270 dpi can be exposed. These are 859 mm per minute.

System Description

High precision laser recorder

Light source

Laser diode emissions at 670 - 680 nm

Imaging principle

Light beam deflected by a rotating, air-cushioned prism;
Inner drum principle

Maximum format size

762 x 558mm (30 x 22 inch)

Imaging format Herkules BASIC

750 x 558 mm (29.5 x 21.9 inch)

Scan line length of 558 mm (inner drum circumference)

Resolution and recorder speed

resolution. Max. Speed

Pixel/cm Dots/inch cm/min inch/min

333 846 96,7 38,1

500 1270 64,4 25,4

666 1693 48,3 19,0

800 2032 40,2 15,8

1000 2540 32,2 12,7

1333 3387 24,1 9,5

Spot sizes

fixed spot sizes 20 and 30 µm

Maximum screen frequency

Up to 80 l/cm (210 lpi) for 256 gray levels

Repeat accuracy

± 5 µm over full format and eight color separations (color set)

imaged in direct succession and ignoring distortion of photographic material caused by changes in temperature and humidity

Output options

positive, negative, right and wrong reading and Duplo, double-Duplo and Quadro

Photographic materials in roll-form

Film, RC paper, direct print films, 0.1 - 0.18 mm thick;

Sensitivity to light emission at 670 - 680 nm

Material widths

Herkules BASIC with lateral material positioning:

280-762 mm with spacing of 30 mm (11 - 30 inch)

Herkules BASIC with central material positioning:

430-762 mm with spacing of 30 mm (17-30 inches)

Photographic material specifications

Internal diameter of cardboard core 72 mm with special end caps;

Emulsion outside, special packaging for insertion into the supply cassette during daylight

Capacity of supply cassette

max. 60 m with 0.10 mm thick photographic material, dependent on material

Capacity of the receiving box

about 20 m with 0.10 mm thick photographic material, dependent on material

Mains voltage

115 or 230 volts AC

Power

1.0 KW at 115 V, 1.2 kW at 230 V

Ambient temperature

+18 ° C to +28 ° C

Humidity

45-85%, non-condensing

Dimensions (W x H x D)

1510 x 930 x 780 mm (59.4 x 36.6 x 30.7 inch)

Weight

approx. 510 kg

Interfaces

SpeedWay interface = high-speed interface for bitmap transmission and Communications interface;

= X69 interface for online processor



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MWSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG**
Klönnestraße 94
D-44143 Dortmund

BRAKENSIEK®
SYSTEMHAUS



www.brakensiek.com

Tim Brakensiek



 **+49(0)231.985-00 10**



 **+49(0)231.985-2000**