

Heidelberg Prosetter 74 Halbautomat



Heidelberg Prosetter 74 Half Automatic

Non-new

Year: 2003

The future is owned by Computer to Plate:

The illuminators of the Prosetter family offer everything you can imagine concerning efficiency: modularity, security, automation and quality.

Economic CTP Production:

The Prosetter revs your production.

The main advantages are the cheap violet technology, the easy handling and plate up to the full upgradability automation. Convenient plate handling. The loading system Allows for easy handling and quick plate in natural light ambience. In addition, there is the upgradability up to the heavy duty fully automatic machine capable with the Single Cassette Loader (SCL) or the Multi Cassette Loader (MCL). Another advantage is that you can use with the Prosetter SCL and MCL in natural light ambiances. Equipped with a SCL or a MCL, the Prosetter grants even more comfort and security.

Quality:

The architecture of the inner drum offers you the precision you are accustomed to from Heidelberg. On all models the Prosetter pressure plate are adjusted very PRECISELY during exposure and are fixed in a hollow by a vacuum. The laser moves along this hollow and illuminates the plate point by point. The laser point is deflected by a rotating prism and reaches, through that, up to a thousandth of millimeter accuracy.

Technical Data:

Base Unit:

4-sided Plateilluminator,

Inner-drum illumination principle.

Plate cassette capacity each:

up to 100 plates (0.30 mm thickness),

up to 150 plate (0.15 mm thickness)

Measurements (W x D x H):

1730 x 1385 x 1,560 mm

Resolution:

2.400 / 2.540 / 3386 dpi

Laser Type:

Violet laser diode, 405 nm, 30 mW (for

Silverhalogenideplates customizable to 5 mW),

Laser Class 1

Illumination range (H x W):

max. 645 x 750 mm

Pressure Plate Size (W x H):

min. 370 x 323 mm

max. 670 x 750 mm

Productivity (plates / hour with 2,540 dpi):
Up to 16 (Prosetter 74)

Weight:
475 kg

Current supply:
200 - 240 V alternating current, 1.2 kW, 5 A

Environmental conditions:
Working temperature: 18 ° C to 28 ° C, 45%
maximum of 80% humidity
(Not condensating).

Allowance / Conformity:
GS, UL, cUL, GOST / CE, FCC, ACN

Supplies:
including Raptor Pro 68 Silver

Premises for connection to the Prinect CP2000 Center
MetaDimension from Version 5.0,
Prinect CP2000 Center from version V41, PresetLink activation

Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MwSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG**
Klönnestraße 94
D-44143 Dortmund

www.brakensiek.com

☎ **+49(0)231.985-00 10**

☎ **+49(0)231.985-2000**

BRAKENSIEK®
SYSTEMHAUS

Tim Brakensiek