

HP ProCurve Switch 2900-24G



HP ProCurve Switch 2900-24G

Product description of the manufacturer:

The ProCurve Switch in 2900 series Switches are equipped with 4 dual Personality ports for 10/100/1000-or Mini-GBIC-Konnektivität. With four integrated to 10-Gigabit Ethernet connections (two CX4 ports and two X2 slots) the series in 2900 offers the biggest flexibility and the best Implementierbarkeit of her class concerning 10-Gigabit Mehrfach-Stacking and-Uplinks. RIP-and static IP-Routing, efficient security functions and administrative functions and the free servicing about the whole life cycle make the series in 2900 cost-effective solutions sure about future for customers whom high-capacity networks build up.

Miscellaneous

Rackmontagesatz: Included

Encryption Algorithm: SSL

Authentication method: RADIUS, TACACS +, Secure Shell v.2 (SSH2)

Product certifications: Class FCC A certificates, CISPR 22 Class A, CISPR 24, EN 60950, EN55022, IEC 61000-3-2, IEC 61000-3-3, IEC 61000-4-11, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, VCCI Class A ITE, IEC 60950, EN55024, UL 60950, CSA 22.2 No. 60950

In general

MPN: J9049A, J9049A#ABB

Device type: Switch - administered - stackable

Kind: Externally - 1U

Width: 44.3 cm

Depth: 39.2 cm

Height: 4.4 cm

Weight: 6.3 kg

Localisation: In English / Europe

Processor

Processor: 1 x Freescale PowerPC: 667 MHz

Memory

RAM: 13.5 MB SDRAM

Flash memory: 4 mb Flash

Network

Anz. Connections: 24 x Ethernet 10Base-T, Ethernet 1000Base-T, Ethernet 100Base-X

Additional Network ports: 2x10GBase-CX4

Data transfer rate: 1 Gbps

Data link Protocol: Ethernet, Almost Ethernet, Gigabit Ethernet

Routing Protocol: Static IP Routing

Remoteverwaltungsprotokoll: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTP

Connection technology: Cables

Switching protocol: Ethernet

Status indicator: Link Activity, connection-transference speed

Achievement signs: River control, BOOTP support, ARP support, VLAN support, Auto-Uplink (car MDI/MDI-X), administerable, IPv6 support

Product certifications: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1x, IEEE 802.1see

Enlargement

Enlargement slots whole (freely):

- * 4 (4) x SFP (mini-GBIC)
- * 2 (2) x X2

Interfaces:

- * 24 x network - Ethernet 10Base-T / 100Base-TX / 1000Base-T - RJ-45
- * 2 x network - Ethernet 10GBase-CX4
- * 1 x serial - RS-232C - D-Sub (DB-9), 9-pole

Electricity supply

Electricity supply device: Electricity supply - inside

Necessary mains voltage: Change stream 120/230 V (50/60 hertz)

Achievement admission in the company: 200 watts

Surroundings terms

Min operating temperature: 0 °C

Max Betriebstemperatur: 55 °C

Allowed air humidity in the company: 15 - 95%



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MwSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG**
Klönnestraße 94
D-44143 Dortmund

BRAKENSIEK®
SYSTEMHAUS



www.brakensiek.com

Tim Brakensiek



 **+49(0)231.985-00 10**



 **+49(0)231.985-2000**