

easyRAID® S6A2-U4R2



easyRAID® S6A2-U4R2

Promise VTrak M300i

Product description of the manufacturer

The system VTrak M300i RAID Storage is conceived for the professional application in modern and highly competitive surroundings IT. The highest achievement is offered by the company of reasonable Serial-ATA hard disks of the newest generation for a favorable price. The management of the VTrak M300i occurs in an easy and clear manner about an embedded, web-based software tool. Associations RAID, LUN Mapping, on-line capacity enlargement, level RAID migration as well as alarm and other system parameters are to be put individually. The highest operational safety and data availability is reached by the application of Promise's PerfectRAID as well as the application of the failure early diagnosis developed by Promise Technology (PDM - Predictive data migration). The systems distinguish themselves friendly design by robust and service. Net parts and fan unities are laid out redundant and are easy in the mistake case to exchange

In general

MPN: P29VM3I20000G02, P29VM3I20000001

Device type: NAS server

Host-Konnektivität: Gigabit Ethernet

Kind: Rack - able of installation - 2U

Number of installed periphery devices / modules: 12 (Maxes) (instal) / 0

Width: 44.6 cm

Depth: 59.7 cm

Height: 8.9 cm

Weight: 21 kg

Mass memory controller

Type: RAID

Controller-interface type: Serial ATA-300, Serial ATA II

Supported devices: Hard disk

RAID Level: RAID 0, RAID 1, RAID 5, RAID 10, RAID 50, RAID 1E

Cache and buffer size (Max): 256 mb (512 mb)

Hard disk

Type: None

Network

Type: Network map

Data link Protocol: Gigabit Ethernet

Network / transport protocol: TCP/IP, iSCSI

Remoteverwaltungsprotokoll: SNMP, Telnet, SNMP, Telnet, CIM, HTTP

Enlargement / konnektivität

Erweiterungseinschübe whole (freely): 12 (12) x Hot-Swap - 8.9 cm x 1/3H (3.5" x 1/3H)

Interfaces:

2 x Ethernet 1000Base-T - RJ-45

1 x serial RS-232 (management) - D-Sub (DB-9), 9-pole

1 x Ethernet (management) - RJ-45

Electricity supply

Electricity supply device: 2 (2) x electricity supply Hot-Plug - plug-in module

Redundant electricity supply: Built-in

Plan for redundant electricity supply: 1+1

Necessary mains voltage: Change stream 120/230 V (50/60 hertz)

Achievement admission in the company: 340 watts

Put achievement: 360 watts

Software

Software included: Driver & Utilities

Necessary operating system: Microsoft Windows 2000, Red Having Linux, SuSe Linux, Apple MacOS X, Microsoft Windows Server 2003

Manufacturer's guarantee

Service & Support: 3-year guarantee

Details to service & Support: Restricted guarantee - 3 years

Surroundings terms

Min operating temperature: 5 °C

Max Betriebstemperatur: 40 °C

Miscellaneous

Product certifications: CE, class FCC A certificates, VCCI, BSMI, MIC

Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MwSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG**
Klönnestraße 94
D-44143 Dortmund

www.brakensiek.com

 **+49(0)231.985-00 10**

 **+49(0)231.985-2000**

BRAKENSIEK®
SYSTEMHAUS

Tim Brakensiek