

X-Rite 530 Spektraldensitometer



X-Rite 530 Spectrodensitometer

Advanced spectrodensitometer for pressroom, ink lab or testing lab providing spectral, color, and density measurements. Connects to X-Rite's IntelliTrax auto scanning system, and complements X-Rite's ColorMaster, InkFormulation and other software applications.

Functions

[X] Density

[X] Color*

[X] Match*

[X] Dot

[X] Trap

[X] Print Contrast

[X] Hue Error / Grayness

[X] Paper Indices

[X] Compare

[X] Electronic Function Select (EFS)

*Contains reflectance values ??and graphical representation

Specifications

Measurement conditions

Illuminant types:	A, C, D50, D55, D65, D75, F2, F7, F11, F12
Standard observers:	2°, 10°
Response types:	ISO Status T, ISO Status E, ISO Status I, ISO Status A, G, Tx, Ax, Ex, Hi-Fi

Measurement technology

Spectral range:	400nm to 700nm
Measurement geometry:	45°/0° per ANSI, DIN & ISO Standards
Measurement aperture:	3.4mm (.13in) standard
	2.0mm (.078in) optional
	6.0mm (.236in) optional
	Micro-Spot: 1.6mm (.063in, H) x 3.2mm (.125in, W) optional
Light source:	Gas Pressure @ 2856°
Physical filters:	No (incandescent lamp light), Optional Polarized, Optional UV cutoff
Measurement time:	Approx. 1.4 seconds per single measurement
	Approx. 0.9 seconds in Speed Read mode
Measurement range:	0.00D–2.5D; 0–160%R

Inter-instrument agreement: ± 0.01 D or 1% for typical printing processes

0.40 ?E CMC MAX on 12 BCRA Tiles

Density repeatability: ± 0.005 D for 0.00–2.00 D*

± 0.010 D for 2.00–2.50 D*

*Polarized Yellow: ± 0.010 D for 0.00–1.80 D

Micro-Spot: ± 0.010 D for 0.0–1.8 D

Data interface

Serial data interface: RS-232 with baud rates 1200 to 57.6K

Power supply

Power source: Ni-MH battery pack, 4.8v rated @ 1650mAh

Charge time: Approximately 3 hours

Environmental

Operating temperature: $+10^{\circ}$ to $+35^{\circ}$ C

Humidity: 30%–85% RH non condensing

Mechanical data

Physical dimensions: Length: 197mm (7.8in) Width: 76mm (3.0in) Height: 81mm (3.2in)

Weight: 1050 grams (2.3lbs.)

BRAKENSIEK®
SYSTEMHAUS



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MwSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG**
Klönnestraße 94
D-44143 Dortmund

BRAKENSIEK®
SYSTEMHAUS



www.brakensiek.com

Tim Brakensiek



 **+49(0)231.985-00 10**



 **+49(0)231.985-2000**